





ROTOR Spacers: 0,5 mm | 2 mm | 3 mm | 8 mm | 11 mm
Choose your combination to fill the spaces L and R



			CHAIN LINE 49 135mm axle		CHAIN LINE 52 141mm axle		CHAIN LINE 55 147mm axle	
Frame		Bottom Bracket	L (mm)	R (mm)	L (mm)	R (mm)	L (mm)	R (mm)
BSA	D Thread 1.37"x24TPI / W 68mm	BSA30	8.5	2	11.5	5	14.5	8
	W 73mm	BSA30	5.5	0	9	2.5	12	5.5
	W 73mm Cannondale® Ai	BSA30	3.5	2	6.5	5	9.5	8
BB30-73	D 42mm / W 73mm	BB30	17	11	20	14	Not compatible	
	D 42mm / W 73mm Cannondale® Ai	BB30	14.5	13.5	Not compatible		Not compatible	
BB30-83	D 42mm / W 83mm	BB30	12	6	15	9	18	12
	D 42mm / W 83mm Cannondale® Ai	BB30	9.5	8.5	12.5	11.5	15.5	14.5
BB30-84	D 42mm / W 84mm	BB30	11.5	5	14.5	8	17.5	11
PF30-73	D 46mm / W 73mm	PF4630	17	11	20	14	Not compatible	
		UBB4630 PF30	5.5	0	9	2.5	12	5.5
PF30-73Ai	D 46mm / W 73mm Cannondale® Ai	PF4630	14.5	13.5	Not compatible		Not compatible	
		UBB4630 PF30	3.5	2	6.5	5	9.5	8
PF30-83	D 46mm / W 83mm	PF4630	12	6	15	9	18	12
		UBB4630 BB386	12	6	15	9	7	0.5
		UBB4630 PF30	Not compatible		Not compatible			
PF30-83Ai	D 46mm / W 83mm Cannondale® Ai	PF4630	9.5	8.5	12.5	11.5	15.5	14.5
		UBB4630 BB386	9.5	8.5	1.5	0	4.5	3
		UBB4630 PF30	Not compatible					
OSBB-84	D 46mm / W 84.5mm Specialized®	PF4630	11.5	5	14.5	8	17.5	11
		UBB4630 PF386	11.5	5	14.5	8	6	0
		UBB4630 PF30	Not compatible		Not compatible			
BB89	D 46mm / W 89.5	PF4130	6.5	0.5	9.5	3.5	12.5	6.5
BB92	D 46mm / W 92mm Asym. NDS 44.75mm	PF4130	Not compatible		9.5	1	12.5	4
BBRight	D 46mm / W 79mm	UBB4630 BBRight	8.5	2	0.5	5	3.5	8
		UBB4630 PF30	Not compatible					
BB392EVO	D 46mm / W 91.5mm	PF4630	8	1.5	11	4.5	14	7.5
		UBB4630 BB386	8	1.5	11	4.5	14	7.5
T47-73	D T47 Thread / W 73mm	T4730 External	5.5	0	9	2.5	12	5.5
T47-83	D T47 Thread / W 83mm	T4730 Internal	12	6	15	9	7	0.5
		T4730 External	Not compatible		Not compatible			
T47-89.5	D T47 Thread / W 89.5mm	T4730 Internal	9	2.5	12	5.5	15	8.5
T47-92	D T47 Thread / W 92mm	T4730 Internal	7.5	1.5	10.5	4.5	13.5	7.5
T47-100	D T47 Thread / W 100mm	T4730 Internal	Not compatible		6.5	0.5	9.5	3.5

ROTOR Spacers: 0,5 mm | 2 mm | 3 mm | 8 mm | 11 mm
Choose your combination to fill the spaces L and R



			CHAIN LINE 52 135mm axle		CHAIN LINE 55 141mm axle		CHAIN LINE 56.5 144mm axle	
			L (mm)	R (mm)	L (mm)	R (mm)	L (mm)	R (mm)
Frame		Bottom Bracket						
BSA	D Thread 1.37"x24TPI / W 68mm	BSA30	5.5	5	8.5	8	10	9.5
	W 73mm	BSA30	3	2.5	6	5.5	7.5	7
	W 73mm Cannondale® Ai	BSA30	0.5	5	3.5	8	5	9.5
BB30-73	D 42mm / W 73mm	BB30	13.5	14	Not compatible		Not compatible	
	D 42mm / W 73mm Cannondale® Ai	BB30	Not compatible		Not compatible		Not compatible	
BB30-83	D 42mm / W 83mm	BB30	8.5	9	11.5	12	13	13.5
	D 42mm / W 83mm Cannondale® Ai	BB30	6	11.5	9	14.5	10.5	16
BB30-84	D 42mm / W 84mm	BB30	8	8	11	11	12.5	12.5
PF30-73	D 46mm / W 73mm	PF4630	13.5	14	Not compatible		Not compatible	
		UBB PF30	3	2.5	6	5.5	7.5	7
PF30-73Ai	D 46mm / W 73mm Cannondale® Ai	PF4630	Not compatible		Not compatible		Not compatible	
		UBB PF30	0.5	8	3.5	8	5	9.5
PF30-83	D 46mm / W 83mm	PF4630	8.5	9	11.5	12	13	13.5
		UBB BB386	8.5	9				
		UBB PF30	Not compatible		1	0.5	2.5	2
PF30-83Ai	D 46mm / W 83mm Cannondale® Ai	PF4630	6	11.5	9	14.5	Not compatible	
		UBB BBright	6.5	0	9.5	3	11	4.5
OSBB-84	D 46mm / W 84.5mm Specialized®	PF4630	8	8	11	11	12.5	12.5
		UBB4630 PF30	Not compatible		0	0	1.5	1.5
BB89	D 46mm / W 89.5	PF4130	3.5	3.5	6.5	6.5	8	8
BB92	D 46mm / W 92mm Asym. NDS 44.75mm	PF4130	3.5	1	6.5	4	8	5.5
BBRight	D 46mm / W 79mm	UBB4630 BBRight	5.5	5	7	6.5	8.5	8
BB392EVO	D 46mm / W 91.5mm	UBB4630 BB386	4.5	4.5	6	6	7.5	7.5
T47-73	D T47 Thread / W 73mm	T4730 Internal	13.5	14	Not compatible		Not compatible	
		T4730 External	3	2.5	6	5.5	7.5	7
T47-83		T4730 Internal	8.5	9	11.5	12	Not compatible	
		T4730 External	Not compatible		1	0.5	2.5	2
T47-89.5	D T47 Thread / W 89.5mm	T4730 Internal	5.5	5.5	8.5	8.5	10	10
T47-92	D T47 Thread / W 92mm	T4730 Internal	4	4.5	7	7.5	8.5	9
T47-100	D T47 Thread / W 100mm	T4730 Internal	0	0.5	3	3.5	4.5	5